

TEST REPORT

1. Applicant

Client Name : FEELUX Co. Ltd.

Address : 235-48 Gwangjeok-ro Gwangjeok-myeon Yangju-si Gyeonggi-do 482-844 Korea

Date of Receipt : 190411

2. Purpose of Report :

3. Test Standard / Item : LED / 190411 LS60 40K-24V-C90-20

4. Test Period : 190411 ~ 190411

5. Test Environment

Ambient Temp. : (0 +- 3) °C

Relative Humidity : (0 +- 10) % RH

6. Test Result : Refer to the attachment

Test Item

Name of Product :

FEELUX

Model / Rating :

Model : FEELUX

Rating :

Confirmation	Test by CGR	Technical manager CGR
--------------	----------------	--------------------------

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This report cannot be reproduced, except in full.

This report is for reference only. It cannot replace the report by standard organization(s).

TEST RESULT

Report Number	Sample Name	Sample Number	Test Standard
190411	FEELUX		LED

Test Item	Unit	Result	Memo
Beam Distribution Test	-	See attachment	
ATHD	%	0.0	
CIE 1931 Cxy		0.3915, 0.3934	
Correlated Color Temperature	K	3844	
Ra	-	91.14	
Power Factor	%	1.000	
Input Voltage	V	23.970	
Input Current	A	0.259	
Input Watt	W	6.2	
Lamp Flux	lm	389.6	
Efficient	lm/W	62.76	
Illuminance	lx	1215	1 m
		304	2 m
		135	3 m


* This test result is for the sample provided by the client.

Sample photo

Click to load image

Luminaire

Lamp	Report	190411
No. of lamps	1 Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190411 LS60 40K-24V-C90-20.jdt	
Lamp flux (lm)	390 Operator	Current (A) 0.259 CGR
Total flux (lm)	390 Date	Power Factor 1 2019-04-11 오전 10:12:49




All luminous intensity values are in Cd/KLm unit.

Luminaire

Lamp	Report	190411
No. of lamps	1 Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190411 LS60 40K-24V-C90-20.jdt	
Lamp flux (lm)	390 Operator	Current (A) 0.259 CGR
Total flux (lm)	390 Date	Power Factor 1 2019-04-11 오전 10:12:49

Luminous Intensity Distribution (Lowest 10%)



All luminous intensity values are in Cd/Klm unit.

Luminaire

Lamp	Report	190411
No. of lamps	1 Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190411 LS60 40K-24V-C90-20.jdt	
Lamp flux (lm)	390 Operator	Current (A) 0.259 CGR
Total flux (lm)	390 Date	Power Factor 1 2019-04-11 오전 10:12:49

Luminous Intensity Data

GWC	0	30	60	90	120	150	180	210	240	270	300
0	1214.75	1145.24	1298.54	1048.04	1290.75	1182.01	1214.75	1145.24	1298.54	1048.04	1290.75
10	853.11	720.10	722.06	679.11	744.85	715.49	618.23	751.81	753.26	923.16	861.10
20	436.21	401.29	370.83	310.61	264.98	215.36	173.10	177.26	184.89	224.54	272.20
30	128.71	127.41	119.01	90.92	74.88	60.28	49.94	48.79	52.70	59.68	69.91
40	35.25	32.31	30.88	29.01	27.10	25.81	26.68	25.45	25.68	27.20	27.80
50	28.45	28.23	28.22	26.08	23.38	21.38	21.63	21.07	20.68	21.02	22.35
60	21.61	20.22	18.21	15.51	14.46	11.81	12.38	13.71	14.69	16.01	16.65
70	8.22	7.01	6.73	5.47	4.66	4.31	5.24	5.70	4.41	5.58	6.66
80	2.91	2.66	3.01	1.94	2.28	1.45	1.27	1.66	1.80	2.47	2.67
90	0.05	-0.37	-0.68	0.40	0.39	0.57	-0.36	0.30	-0.41	0.49	0.20
100	0.76	0.07	0.29	-0.26	0.63	0.04	-0.06	0.87	0.12	-0.27	0.23
110	0.17	-0.17	0.08	-0.61	1.07	0.08	-0.01	0.26	0.53	0.29	0.39
120	0.74	0.17	0.42	0.50	0.58	0.61	0.76	0.66	0.60	1.16	0.34
130	0.76	0.64	0.65	1.08	0.64	1.66	1.60	0.66	1.48	1.27	0.89

Luminaire

Lamp	Report			190411
No. of lamps	1 Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190411 LS60 40K-24V-C90-20.jdt			
Lamp flux (lm)	390 Operator	Current (A)	0.259	CGR
Total flux (lm)	390 Date	Power Factor	1	2019-04-11 오전 10:12:49

Luminous Intensity Data (Continued)

GWC	330	360
0	1182.01	1214.75
10	883.24	853.11
20	331.77	436.21
30	91.39	128.71
40	29.25	35.25
50	23.01	28.45
60	17.92	21.61
70	7.80	8.22
80	2.47	2.91
90	0.66	0.05
100	0.64	0.76
110	0.00	0.17
120	-0.25	0.74
130	1.29	0.76

Luminaire

Lamp	Report	190411
No. of lamps	1 Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190411 LS60 40K-24V-C90-20.jdt	
Lamp flux (lm)	390 Operator	Current (A) 0.259 CGR
Total flux (lm)	390 Date	Power Factor 1 2019-04-11 오전 10:12:49

Luminous Flux Table


Total Lamp Lumens: 390
 Luminaire Efficiency (lm/W):389.62
 CIE Classification: Direct

Elevation	Lumens	Cumulative	Lamp %	Luminaire %
0	28.61	28.61	7.34	7.34
10	146.21	174.82	44.87	44.87
20	104.98	279.80	71.82	71.81
30	44.43	324.23	83.22	83.22
40	20.09	344.32	88.38	88.37
50	19.96	364.28	93.50	93.50
60	15.27	379.55	97.42	97.42
70	6.16	385.71	99.00	99.00
80	2.39	388.10	99.61	99.61
90	0.11	388.21	99.64	99.64
100	0.28	388.49	99.71	99.71
110	0.18	388.67	99.76	99.76
120	0.50	389.16	99.89	99.88
130	0.46	389.62	100.01	100.00

Luminaire

Lamp	Report	190411
No. of lamps	1 Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190411 LS60 40K-24V-C90-20.jdt	
Lamp flux (lm)	390 Operator	Current (A) 0.259 CGR
Total flux (lm)	390 Date	Power Factor 1 2019-04-11 오전 10:12:49


IsoCandela (Type C)



Luminaire

Lamp	Report	190411
No. of lamps	1 Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190411 LS60 40K-24V-C90-20.jdt	
Lamp flux (lm)	390 Operator	Current (A) 0.259 CGR
Total flux (lm)	390 Date	Power Factor 1 2019-04-11 오전 10:12:49

IsoLux Diagram (Ground)




Pole Height (m): 2.7

Area Width (m): 12

Luminaire

Lamp	Report	190411
No. of lamps	1 Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190411 LS60 40K-24V-C90-20.jdt	
Lamp flux (lm)	390 Operator	Current (A) 0.259 CGR
Total flux (lm)	390 Date	Power Factor 1 2019-04-11 오전 10:12:49

IsoLux Diagram (Wall)



Pole Height (m): 2.7 Wall Distance (m): 2.7
Aiming Plane: 0 Wall Height (m): 12

Luminaire

Lamp

No. of lamps	1	Voltage (V)	23.97
Lamp flux (lm)	390	Current (A)	0.259
Total flux (lm)	390	Power Factor	1

Report

190411

Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190411 LS60 40K-24V-C90-20.jdt

Operator

CGR

Date

2019-04-11 오전 10:12:49

Illuminance Levels (Ground)

6.00	0.05	0.07	0.03	0.05	0.07	0.10	0.09	0.09	0.09	0.07	0.04	0.08	0.07
5.00	0.06	0.04	0.07	0.10	0.26	0.36	0.36	0.35	0.31	0.13	0.08	0.05	0.10
4.00	0.03	0.05	0.22	0.35	0.30	0.46	0.47	0.45	0.40	0.39	0.27	0.09	0.05
3.00	0.05	0.08	0.30	0.37	0.82	0.92	1.09	1.07	0.89	0.48	0.40	0.15	0.07
2.00	0.06	0.24	0.29	0.73	1.17	1.83	3.59	2.23	1.37	0.97	0.40	0.32	0.10
1.00	0.07	0.28	0.34	0.86	1.80	12.51	75.47	18.74	2.27	1.07	0.49	0.34	0.11
0.00	0.08	0.30	0.39	0.93	2.47	68.31	166.63	94.98	4.82	1.22	0.59	0.40	0.13
-1.00	0.07	0.27	0.34	0.81	1.66	7.53	101.87	10.30	1.86	0.86	0.49	0.35	0.12
-2.00	0.07	0.23	0.27	0.74	1.04	1.65	2.74	1.83	1.08	0.80	0.33	0.26	0.08
-3.00	0.05	0.09	0.30	0.32	0.71	0.79	0.91	0.83	0.75	0.37	0.32	0.13	0.06
-4.00	0.03	0.06	0.19	0.29	0.28	0.39	0.43	0.39	0.33	0.30	0.21	0.08	0.05
-5.00	0.06	0.04	0.06	0.10	0.23	0.28	0.30	0.28	0.25	0.11	0.07	0.04	0.08
-6.00	0.04	0.06	0.03	0.05	0.07	0.09	0.09	0.08	0.08	0.06	0.04	0.07	0.05
-6.00	-5.00	-4.00	-3.00	-2.00	-1.00	0.00	1.00	2.00	3.00	4.00	5.00	6.00	

Illum. (Max.): 167

All illuminance level values are in lux.

Illum. (Min.): 0.03

Illum. Avg.: 3.74


Total Optical Solution Provider


<http://www.jnctech.co.kr>
J & C Technology Co., Ltd.

Luminaire

Lamp	Report			190411
No. of lamps	1 Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190411 LS60 40K-24V-C90-20.jdt			
Lamp flux (lm)	390 Operator	Current (A)	0.259	CGR
Total flux (lm)	390 Date	Power Factor	1	2019-04-11 오전 10:12:49

Illuminance Cone Diagram



Luminaire

Lamp				Report	190411
No. of lamps	1	Voltage (V)	23.97	Filename	C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190411 LS60 40K-24V-C90-20.jdt
Lamp flux (lm)	390	Current (A)	0.259	Operator	CGR
Total flux (lm)	390	Power Factor	1	Date	2019-04-11 오전 10:12:49

Coefficient of Utilization

Refl. Ceiling (%)	80%	80%	80%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	10%	0%
Refl. Wall (%)	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
Eff. Floor Cavity Refl.	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%
Room CR 0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 2	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 3	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 4	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 6	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 7	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 8	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 9	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00