

TEST REPORT

1. Applicant

Client Name : FEELUX Co. Ltd.
Address : 235-48 Gwangjeok-ro Gwangjeok-myeon Yangju-si Gyeonggi-do 482-844 Korea
Date of Receipt : 190415

2. Purpose of Report :

3. Test Standard / Item : LED / 190415 MNP8 40K-24V-C90

4. Test Period : 190415 ~ 190415

5. Test Environment

Ambient Temp. : (0 +- 3) °C
Relative Humidity : (0 +- 10) % RH

6. Test Result : Refer to the attachment

Test Item

Name of Product :

FEELUX

Model / Rating :

Model : FEELUX

Rating :

Confirmation	Test by CGR	Technical manager CGR
--------------	----------------	--------------------------

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
This report cannot be reproduced, except in full.
This report is for reference only. It cannot replace the report by standard organization(s).

TEST RESULT

Report Number	Sample Name	Sample Number	Test Standard
190415	FEELUX		LED

Test Item	Unit	Result	Memo
Beam Distribution Test	-	See attachment	
ATHD	%	0.0	
CIE 1931 Cxy		0.3847, 0.3809	
Correlated Color Temperature	K	3925	
Ra	-	93.49	
Power Factor	%	1.000	
Input Voltage	V	23.960	
Input Current	A	0.356	
Input Watt	W	8.53	
Lamp Flux	lm	722.4	
Efficient	lm/W	84.69	
Illuminance	lx	196	1 m
		49	2 m
		22	3 m


* This test result is for the sample provided by the client.

Sample photo

Click to load image

Luminaire


Lamp	Report	190415
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190415 MNP8 40K-24V-C90.jdt
Lamp flux (lm)	722	Operator Current (A) 0.356 CGR
Total flux (lm)	722	Date Power Factor 1 2019-04-15 오후 12:17:12



All luminous intensity values are in Cd/Klm unit.

Luminaire

Lamp	Report	190415
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190415 MNP8 40K-24V-C90.jdt
Lamp flux (lm)	722	Operator Current (A) 0.356 CGR
Total flux (lm)	722	Date Power Factor 1 2019-04-15 오후 12:17:12



All luminous intensity values are in Cd/KLm unit.

Luminaire

Lamp		Report			190415
No. of lamps	1	Filename	C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190415 MNP8 40K-24V-C90.jdt		
Lamp flux (lm)	722	Operator	Current (A)	0.356	CGR
Total flux (lm)	722	Date	Power Factor	1	2019-04-15 오후 12:17:12

Luminous Intensity Data

GWC	0	30	60	90	120	150	180	210	240	270	300	330	360
0	195.65	194.98	194.65	193.99	193.03	193.84	195.65	194.98	194.65	193.99	193.03	193.84	195.65
10	194.12	192.71	192.39	190.11	191.57	192.05	193.17	192.31	190.81	190.14	191.37	192.08	194.12
20	189.11	186.45	183.69	180.65	182.78	185.69	187.08	185.16	181.36	179.95	181.89	184.87	189.11
30	177.02	175.19	169.59	164.07	168.92	172.78	174.58	173.04	166.94	162.41	167.00	173.48	177.02
40	162.23	157.42	150.82	142.66	149.92	155.75	157.23	153.87	147.29	141.23	148.46	155.38	162.23
50	141.44	136.36	126.54	117.61	125.67	134.09	135.11	131.90	122.68	114.70	123.36	134.20	141.44
60	117.33	111.60	99.25	87.69	98.13	109.30	109.71	106.16	94.99	84.48	95.98	108.28	117.33
70	88.85	83.16	70.08	55.38	68.21	79.32	80.64	77.15	64.51	51.61	66.11	80.44	88.85
80	59.44	53.16	39.04	23.02	37.83	50.38	52.01	47.60	33.16	19.79	35.34	50.39	59.44
90	39.29	33.60	18.00	2.58	17.24	31.53	36.72	31.66	16.63	0.85	18.05	31.96	39.29
100	37.55	32.12	17.78	1.78	17.10	31.26	36.00	30.37	15.54	0.16	17.80	31.92	37.55
110	36.07	30.97	16.97	0.68	16.31	29.71	34.01	29.32	10.68	0.88	15.82	30.14	36.07
120	30.40	24.46	1.51	1.73	1.44	23.28	27.28	21.26	1.63	1.70	1.36	24.07	30.40
130	20.04	11.22	8.86	1.42	9.00	10.20	17.97	12.51	7.46	1.63	8.75	12.52	20.04

Luminaire

Lamp	Report	190415
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190415 MNP8 40K-24V-C90.jdt
Lamp flux (lm)	722	Operator Current (A) 0.356 CGR
Total flux (lm)	722	Date Power Factor 1 2019-04-15 오후 12:17:12

Luminous Flux Table


Total Lamp Lumens: 722
 Luminaire Efficiency (lm/W): 722.41
 CIE Classification: Direct

Elevation	Lumens	Cumulative	Lamp %	Luminaire %
0	4.65	4.65	0.64	0.64
10	36.50	41.14	5.70	5.70
20	68.95	110.09	15.24	15.24
30	93.32	203.41	28.16	28.16
40	106.91	310.32	42.96	42.96
50	107.93	418.25	57.90	57.90
60	96.66	514.91	71.28	71.28
70	74.23	589.13	81.55	81.55
80	45.04	634.18	87.79	87.79
90	25.38	659.56	91.30	91.30
100	24.21	683.77	94.65	94.65
110	21.58	705.35	97.64	97.64
120	12.66	718.00	99.39	99.39
130	4.41	722.41	100.00	100.00

Luminaire

Lamp	Report	190415
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190415 MNP8 40K-24V-C90.jdt
Lamp flux (lm)	722	Operator Current (A) 0.356 CGR
Total flux (lm)	722	Date Power Factor 1 2019-04-15 오후 12:17:12

IsoCandela (Type C)




0 ~ 20	98 ~ 117
20 ~ 39	117 ~ 137
39 ~ 59	137 ~ 157
59 ~ 78	157 ~ 176
78 ~ 98	176 ~ 196

Luminaire

Lamp	Report	190415
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190415 MNP8 40K-24V-C90.jdt
Lamp flux (lm)	722	Operator Current (A) 0.356 CGR
Total flux (lm)	722	Date Power Factor 1 2019-04-15 오후 12:17:12

IsoLux Diagram (Ground)




Pole Height (m): 2.7

Area Width (m): 12

Luminaire

Lamp	Report	190415
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190415 MNP8 40K-24V-C90.jdt
Lamp flux (lm)	722	Operator Current (A) 0.356 CGR
Total flux (lm)	722	Date Power Factor 1 2019-04-15 오후 12:17:12



Pole Height (m): 2.7 Wall Distance (m): 2.7
Aiming Plane: 0 Wall Height (m): 12

Luminaire

Lamp				Report	190415
No. of lamps	1	Voltage (V)	23.96	Filename	C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190415 MNP8 40K-24V-C90.jdt
Lamp flux (lm)	722	Current (A)	0.356	Operator	CGR
Total flux (lm)	722	Power Factor	1	Date	2019-04-15 오후 12:17:12

Illuminance Levels (Ground)

6.00	0.33	0.42	0.35	0.52	0.61	0.71	0.65	0.66	0.72	0.62	0.43	0.48	0.41
5.00	0.49	0.40	0.55	0.73	1.41	1.65	1.66	1.62	1.54	0.86	0.66	0.55	0.54
4.00	0.47	0.68	1.19	1.69	1.89	2.32	2.40	2.31	2.14	1.83	1.40	0.77	0.53
3.00	0.54	0.95	1.88	2.12	4.01	4.65	5.03	5.02	4.26	2.56	2.01	1.04	0.64
2.00	0.68	1.47	1.94	4.37	5.90	9.39	10.68	9.86	6.62	4.58	2.18	1.60	0.78
1.00	0.84	1.82	2.65	4.88	9.48	16.22	21.47	17.05	9.94	5.23	2.72	1.85	0.86
0.00	0.88	1.93	2.88	5.73	11.62	21.83	26.84	21.94	11.91	5.98	3.05	2.02	0.96
-1.00	0.84	1.82	2.65	5.04	9.71	16.85	21.47	16.07	9.40	4.83	2.73	1.88	0.89
-2.00	0.73	1.53	2.07	4.43	6.39	9.64	10.58	9.29	5.80	4.36	1.90	1.45	0.67
-3.00	0.59	0.96	1.92	2.43	4.15	4.86	4.93	4.55	3.95	2.07	1.88	0.95	0.52
-4.00	0.48	0.71	1.34	1.77	2.04	2.23	2.32	2.24	1.85	1.65	1.16	0.68	0.47
-5.00	0.51	0.51	0.62	0.81	1.49	1.57	1.62	1.60	1.38	0.69	0.52	0.38	0.49
-6.00	0.39	0.46	0.40	0.58	0.68	0.63	0.62	0.67	0.58	0.50	0.33	0.41	0.32
-6.00	-5.00	-4.00	-3.00	-2.00	-1.00	0.00	1.00	2.00	3.00	4.00	5.00	6.00	

Illum. (Max.): 26.8

All illuminance level values are in lux.

Illum. (Min.): 0.32

Illum. Avg.: 3.38


Total Optical Solution Provider


<http://www.jnctech.co.kr>
J & C Technology Co., Ltd.

Luminaire

Lamp	Report				190415
No. of lamps	1	Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190415 MNP8 40K-24V-C90.jdt			
Lamp flux (lm)	722	Operator	Current (A)	0.356	CGR
Total flux (lm)	722	Date	Power Factor	1	2019-04-15 오후 12:17:12

Illuminance Cone Diagram



Beam Angle = 131 deg.

Based on 50% of maximum illuminance.

Luminaire

Lamp

Report

190415

No. of lamps 1 Voltage (V) 23.96

Filename C:\Users\WFEELUX\Desktop\완료 리포트\Data\2019\190415 MNP8 40K-24V-C90.jdt

Lamp flux (lm) 722 Current (A) 0.356

Operator CGR

Total flux (lm) 722 Power Factor 1

Date 2019-04-15 오후 12:17:12

Coefficient of Utilization

Refl. Ceiling (%)	80%	80%	80%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	10%	0%
Refl. Wall (%)	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
Eff. Floor Cavity Refl.	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%
Room CR 0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 2	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 3	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 4	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 6	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 7	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 8	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 9	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00